

Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

TM DESANA MAX CL

Version number: GHS 1.0

Date of compilation: 2019-03-15

SECTION 1: Identification

1.1 Product identifier

Trade name

TM DESANA MAX CL

1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses

biocidal product
cleaning agent
professional use (SU22)
industrial use (SU3)

Uses advised against

do not use for squirting or spraying
do not use for products which come into direct contact with the skin

1.3 Details of the supplier of the safety data sheet

Thonhauser GmbH
Perlhofgasse 2/1
2372 Giesshübl/Wien
Austria

Telephone: +43 (0)2236 320 272
Telefax: +43 (0)2236 320 273
e-mail: QA@thonhauser.net
Website: www.thonhauser.net

e-mail (competent person)

QA@thonhauser.net (Herr Dr. Daniel Herzog)

1.4 Emergency telephone number

Manufacturer

+43 699 141 80 200

Mon - Thu 07:00 - 15:00, Fri 07:00 - 13:00

Poison center & Emergency information service

United States	Chemtrec Emergency Customer #CCN837	1-800-424-9300 (24h)
---------------	-------------------------------------	----------------------

SECTION 2: Hazard(s) identification

2.1 Classification of the substance or mixture

Classification acc. to GHS

Section	Hazard class	Cat-egory	Hazard class and category	Hazard state-ment
2.16	Substance or mixture corrosive to metals	1	Met. Corr. 1	H290
3.2	Skin corrosion/irritation	1A	Skin Corr. 1A	H314
3.3	Serious eye damage/eye irritation	1	Eye Dam. 1	H318
4.1C	Hazardous to the aquatic environment - chronic hazard	2	Aquatic Chronic 2	H411

For full text of H-phrases: see SECTION 16.

The most important adverse physicochemical, human health and environmental effects

Skin corrosion produces an irreversible damage to the skin; namely, visible necrosis through the epidermis and into the dermis. Spillage and fire water can cause pollution of watercourses.

2.2 Label elements

Labeling

- Signal word **danger**

Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

TM DESANA MAX CL

Version number: GHS 1.0

Date of compilation: 2019-03-15

- Pictograms

GHS05, GHS09



- Hazard statements

H290 May be corrosive to metals.
 H314 Causes severe skin burns and eye damage.
 H411 Toxic to aquatic life with long lasting effects.

- Precautionary statements

P260 Do not breathe dust/fume/gas/mist/vapours/spray.
 P273 Avoid release to the environment.
 P280 Wear protective gloves/protective clothing/eye protection/face protection.
 P301+P330+P331 IF SWALLOWED: rinse mouth. Do NOT induce vomiting.
 P303+P361+P353 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.
 P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 P310 Immediately call a POISON CENTER or doctor/physician.
 P321 Specific treatment (see on this label).
 P390 Absorb spillage to prevent material damage.
 P391 Collect spillage.
 P501 Dispose of contents/container to industrial combustion plant.

- Hazardous ingredients for labelling sodium hydroxide

2.3 Other hazards

Results of PBT and vPvB assessment

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

SECTION 3: Composition/information on ingredients

3.1 Substances

not relevant (mixture)

3.2 Mixtures

Description of the mixture

Name of sub-stance	Identifier	Conc.	Classification acc. to GHS	Pictograms	M-Factors
Sodium hydroxide	CAS No 1310-73-2 EC No 215-185-5	50 – < 75 wt%	Met. Corr. 1 / H290 Skin Corr. 1A / H314 Eye Dam. 1 / H318		
Troclosene sodium	CAS No 2893-78-9 EC No 220-767-7	5 – < 10 wt%	Ox. Sol. 2 / H272 Acute Tox. 4 / H302 Acute Tox. 2 / H330 Eye Irrit. 2 / H319 STOT SE 3 / H335 Aquatic Acute 1 / H400 Aquatic Chronic 1 / H410	 	
Sodium perman-ganate	CAS No 10101-50-5 EC No 233-251-1	< 1 wt%	Ox. Sol. 2 / H272 Acute Tox. 4 / H302 Skin Corr. 1B / H314 Eye Dam. 1 / H318 Aquatic Acute 1 / H400 Aquatic Chronic 1 / H410	 	M-Factor (acute) = 10.0

For full text of abbreviations: see SECTION 16.

Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

TM DESANA MAX CL

Version number: GHS 1.0

Date of compilation: 2019-03-15

Regulation 528/2012/EU concerning the making available on the market and use of biocidal products

Biocidal active substances		
Name of substance	W/v	Unit
Troclosene sodium		G/l

SECTION 4: First-aid measures

4.1 Description of first- aid measures



General notes

Do not leave affected person unattended. Remove victim out of the danger area. Keep affected person warm, still and covered. Take off immediately all contaminated clothing. In all cases of doubt, or when symptoms persist, seek medical advice. In case of unconsciousness place person in the recovery position. Never give anything by mouth.

Following inhalation

If breathing is irregular or stopped, immediately seek medical assistance and start first aid actions. In case of respiratory tract irritation, consult a physician. Provide fresh air.

Following skin contact

Rinse skin with water/shower.

Following eye contact

Remove contact lenses, if present and easy to do. Continue rinsing. Irrigate copiously with clean, fresh water for at least 10 minutes, holding the eyelids apart.

Following ingestion

Rinse mouth with water (only if the person is conscious). Do NOT induce vomiting.

4.2 Most important symptoms and effects, both acute and delayed

Symptoms and effects are not known to date.

4.3 Indication of any immediate medical attention and special treatment needed

none

SECTION 5: Fire-fighting measures

5.1 Extinguishing media

Suitable extinguishing media

water, foam, alcohol resistant foam, ABC-powder

Unsuitable extinguishing media

water jet

5.2 Special hazards arising from the substance or mixture

Substance or mixture corrosive to metals.

Hazardous combustion products

nitrogen oxides (NO_x), phosphorus oxides (P_xO_y), hydrogen chloride (HCl)

Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

TM DESANA MAX CL

Version number: GHS 1.0

Date of compilation: 2019-03-15

5.3 Advice for firefighters

In case of fire and/or explosion do not breathe fumes. Co-ordinate firefighting measures to the fire surroundings. Do not allow firefighting water to enter drains or water courses. Collect contaminated firefighting water separately. Fight fire with normal precautions from a reasonable distance.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

Remove persons to safety.

For emergency responders

Wear breathing apparatus if exposed to vapors/dust/aerosols/gases.

6.2 Environmental precautions

Keep away from drains, surface and ground water. Retain contaminated washing water and dispose of it. If substance has entered a water course or sewer, inform the responsible authority.

6.3 Methods and material for containment and cleaning up

Advices on how to contain a spill

covering of drains, take up mechanically

Advices on how to clean up a spill

Take up mechanically. Absorbents and binders, neutralizing agents.

Appropriate containment techniques

Neutralization techniques.

Other information relating to spills and releases

Place in appropriate containers for disposal. Ventilate affected area.

6.4 Reference to other sections

Hazardous combustion products: see section 5. Incompatible substances or mixtures: see section 7. Personal protective equipment: see section 8. Incompatible materials: see section 10. Disposal considerations: see section 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

The product is sold as single-dose units, so handling and risk is reduced. Use general precautions for handling of chemical products. .

Recommendations

- Measures to prevent fire as well as aerosol and dust generation

Use local and general ventilation. Take precautionary measures against static discharge. Use only in well-ventilated areas. Never add water to this product. Ground/bond container and receiving equipment.

- Specific notes/details

Dust deposits may accumulate on all deposition surfaces in a technical room.

- Handling of incompatible substances or mixtures

Do not mix with acids.

- Keep away from

acids

- Advice on general occupational hygiene

Wash hands after use. Do not eat, drink and smoke in work areas. Remove contaminated clothing and protective equipment before entering eating areas. Never keep food or drink in the vicinity of chemicals. Never place chemicals in containers that are normally used for food or drink. Keep away from food, drink and animal feedingstuffs.

Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

TM DESANA MAX CL

Version number: GHS 1.0

Date of compilation: 2019-03-15

7.2 Conditions for safe storage, including any incompatibilities

Managing of associated risks

- Explosive atmospheres

Removal of dust deposits.

- Corrosive conditions

Store in corrosive resistant container with a resistant inner liner.

- Incompatible substances or mixtures

Prohibition of joint storage (with): acids

- Floors

The materials shall display sufficient resistance to the prevalent chemical conditions (Caustic solutions).

- Protect against external exposure, such as

frost

- Consideration of other advice

Observe technical data sheet.

- Ventilation requirements

Use local and general ventilation.

- Specific designs for storage rooms or vessels

Floors: The materials shall display sufficient resistance to the prevalent chemical conditions (Caustic solutions).

- Packaging compatibilities (Receptacles / Material)

Only packagings which are approved (e.g. acc. to the Dangerous Goods Regulations) may be used.

7.3 Specific end use(s)

These information are not available.

7.4 Other information

recommended storage temperature: 0 - 45 °C

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

National limit values

Occupational exposure limit values (Workplace Exposure Limits)											
Cou ntry	Name of agent	CAS No	Iden tifier	TWA [ppm]	TWA [mg/ m ³]	STEL [ppm]	STEL [mg/ m ³]	Ceiling-C [ppm]	Ceiling-C [mg/ m ³]	Nota tion	Sour ce
US	Particulates not otherwise classi-fied (PNOC)		PEL	1,766	15					I, dust	29 CFR 1910.1 000
US	Particulates not otherwise classi-fied (PNOC)		PEL	529.5	5					Partm l, r, dust	29 CFR 1910.1 000
US	Sodium hydroxide	1310-73-2	PEL		2						29 CFR 1910.1 000

Notation

Ceiling-C Ceiling value is a limit value above which exposure should not occur.
dust As dust.

Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

TM DESANA MAX CL

Version number: GHS 1.0

Date of compilation: 2019-03-15

Notation

i	Inhalable fraction.
partml	Particles/ml.
r	Respirable fraction.
STEL	Short-term exposure limit: a limit value above which exposure should not occur and which is related to a 15-minute period (unless otherwise specified).
TWA	Time-weighted average (long-term exposure limit): measured or calculated in relation to a reference period of 8 hours time-weighted average (unless otherwise specified).

Relevant DNELs/DMELs/PNECs and other threshold levels

Relevant DNELs of components of the mixture						
Name of substance	CAS No	End-point	Threshold level	Protection goal, route of exposure	Used in	Exposure time
Sodium hydroxide	1310-73-2	DNEL	1 mg/m ³	Human, inhalatory	Worker (industry)	Chronic - local effects
Sodium permanganate	10101-50-5	DNEL	0.05 mg/m ³	Human, inhalatory	Worker (industry)	Chronic - systemic effects
Sodium permanganate	10101-50-5	DNEL	0.05 mg/m ³	Human, inhalatory	Worker (industry)	Acute - systemic effects

Relevant PNECs of components of the mixture						
Name of substance	CAS No	End-point	Threshold level	Organism	Environmental compartment	Exposure time
Sodium permanganate	10101-50-5	PNEC	0 mg/l	Aquatic organisms	Freshwater	Short-term (single instance)
Sodium permanganate	10101-50-5	PNEC	0 mg/l	Aquatic organisms	Marine water	Short-term (single instance)
Sodium permanganate	10101-50-5	PNEC	1.64 mg/l	Aquatic organisms	Sewage treatment plant (STP)	Short-term (single instance)

8.2 Exposure controls

Appropriate engineering controls

General ventilation.

Individual protection measures (personal protective equipment)



Eye/face protection

Wear eye/face protection. Use safety goggle with side protection. Use protective eyewear to guard against splash of liquids. EN 166.

Skin protection

- Hand protection

When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits. Wear suitable gloves. Chemical protection gloves are suitable, which are tested according to EN 374. Check leak-tightness/impermeability prior to use. In the case of wanting to use the gloves again, clean them before taking off and air them well. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

TM DESANA MAX CL

Version number: GHS 1.0

Date of compilation: 2019-03-15

- Protective gloves - Splash protection

Recommended protective gloves (trademark/manufacturer):

- Other protection measures

Take recovery periods for skin regeneration. Preventive skin protection (barrier creams/ointments) is recommended. Wash hands thoroughly after handling.

Respiratory protection

In case of inadequate ventilation wear respiratory protection. Combination filtering device (EN 141). Particulate filter device (EN 143).

Chemical protective clothing

Wear suitable protective clothing.

Environmental exposure controls

Avoid release to the environment. Refer to special instructions/safety data sheets. Before discharge of the waste water into a municipal waste water treatment facility the product normally needs to be neutralized.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance

Physical state	solid
Color	pink greenish powder
Odor	characteristic

Other safety parameters

pH (value)	12.2 – 13.2 (water: 10 g/l, 20 °C) * (alkaline)
Melting point/freezing point	not determined
Initial boiling point and boiling range	not determined
Flash point	not applicable
Evaporation rate	not determined
Flammability (solid, gas)	non-combustible
Explosion limits of dust clouds	not determined
Vapor pressure	<0.06 Pa at 20 °C
Density	not determined
Vapor density	this information is not available
Bulk density	1.1 – 1.2 g/cm ³
Relative density	information on this property is not available
Solubility(ies)	not determined
Partition coefficient	
- n-octanol/water (log KOW)	this information is not available
Auto-ignition temperature	not determined
Viscosity	not relevant (solid matter)
Explosive properties	none
Oxidizing properties	none

9.2 Other information

Solvent content	0 %
Solid content	100 %

Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

TM DESANA MAX CL

Version number: GHS 1.0

Date of compilation: 2019-03-15

SECTION 10: Stability and reactivity

10.1 Reactivity

Concerning incompatibility: see below "Conditions to avoid" and "Incompatible materials". Substance or mixture corrosive to metals.

10.2 Chemical stability

See below "Conditions to avoid".

10.3 Possibility of hazardous reactions

Exhibits an exothermic reaction (with): acids

Dangerous/dangerous reactions with: base metals (formation of hydrogen)

10.4 Conditions to avoid

There are no specific conditions known which have to be avoided.

10.5 Incompatible materials

There is no additional information.

10.6 Hazardous decomposition products

Reasonably anticipated hazardous decomposition products produced as a result of use, storage, spill and heating are not known. Hazardous combustion products: see section 5.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Test data are not available for the complete mixture.

Classification procedure

The method for classification of the mixture is based on ingredients of the mixture (additivity formula).

Classification acc. to OSHA "Hazard Communication Standard" (29 CFR 1910.1200)

Acute toxicity

Shall not be classified as acutely toxic.

- Acute toxicity estimate (ATE)

Inhalation: dust/mist 2.727 mg/l/4h.

Acute toxicity estimate (ATE) of components of the mixture

Name of substance	CAS No	Exposure route	ATE
Troclosene sodium	2893-78-9	Oral	1,823 mg/kg
Troclosene sodium	2893-78-9	Inhalation: dust/mist	0.27 mg/l/4h
Sodium permanganate	10101-50-5	Oral	500 mg/kg

Skin corrosion/irritation

Causes severe skin burns and eye damage.

Serious eye damage/eye irritation

Causes serious eye damage.

Respiratory or skin sensitization

Shall not be classified as a respiratory or skin sensitizer.

Germ cell mutagenicity

Shall not be classified as germ cell mutagenic.

Carcinogenicity

Shall not be classified as carcinogenic.

Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

TM DESANA MAX CL

Version number: GHS 1.0

Date of compilation: 2019-03-15

Reproductive toxicity

Shall not be classified as a reproductive toxicant.

Specific target organ toxicity - single exposure

Shall not be classified as a specific target organ toxicant (single exposure).

Specific target organ toxicity - repeated exposure

Shall not be classified as a specific target organ toxicant (repeated exposure).

Aspiration hazard

Shall not be classified as presenting an aspiration hazard.

SECTION 12: Ecological information

12.1 Toxicity

Toxic to aquatic life with long lasting effects.

Aquatic toxicity (acute)

Aquatic toxicity (acute) of components of the mixture					
Name of substance	CAS No	Endpoint	Value	Species	Exposure time
Sodium permanganate	10101-50-5	LC50	0.7 mg/l	Fish	48 h
Sodium permanganate	10101-50-5	EC50	0.06 mg/l	Aquatic invertebrates	48 h
Sodium permanganate	10101-50-5	ErC50	0.8 mg/l	Algae	72 h

Aquatic toxicity (chronic) of components of the mixture					
Name of substance	CAS No	Endpoint	Value	Species	Exposure time
Sodium permanganate	10101-50-5	LC50	1.51 mg/l	Fish	24 h
Sodium permanganate	10101-50-5	EC50	0.15 mg/l	Aquatic invertebrates	24 h

12.2 Persistence and degradability

Data are not available.

12.3 Bioaccumulative potential

Data are not available.

12.4 Mobility in soil

Data are not available.

12.5 Results of PBT and vPvB assessment

Data are not available.

12.6 Other adverse effects

Data are not available.

Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

TM DESANA MAX CL

Version number: GHS 1.0

Date of compilation: 2019-03-15

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Waste treatment-relevant information

Recycling/reclamation of other inorganic materials.

Sewage disposal-relevant information

The application solution can be disposed in the sewage system, taking into account technical and national regulations.

Waste treatment of containers/packages

Only packagings which are approved (e.g. acc. to DOT) may be used. Completely emptied packages can be recycled. Handle contaminated packages in the same way as the substance itself.

Remarks

Please consider the relevant national or regional provisions. Waste shall be separated into the categories that can be handled separately by the local or national waste management facilities.


SECTION 14: Transport information

14.1 UN number	3262
14.2 UN proper shipping name	Corrosive solid, basic, inorganic, n.o.s.
Technical name (hazardous ingredients)	sodium hydroxide, troclosene sodium
14.3 Transport hazard class(es)	
Class	8 (corrosive substances)
14.4 Packing group	II (substance presenting medium danger)
14.5 Environmental hazards	hazardous to the aquatic environment (troclosene sodium)
14.6 Special precautions for user	There is no additional information.
14.7 Transport in bulk according to Annex II of MARPOL and the IBC Code	
	The cargo is not intended to be carried in bulk.

Information for each of the UN Model Regulations

Transport of dangerous goods by road or rail (49 CFR US DOT)

Index number	3262
Proper shipping name	Corrosive solid, basic, inorganic, n.o.s.
- Particulars in the shipper's declaration	UN3262, Corrosive solid, basic, inorganic, n.o.s., (contains: sodium hydroxide, troclosene sodium), 8, II, environmentally hazardous
Class	8
Packing group	II
Danger label(s)	8, fish and tree



Environmental hazards
Special provisions (SP)

yes (hazardous to the aquatic environment)
IB8, IP2, IP4, T3, TP33

Safety Data Sheet


acc. to 29 CFR 1910.1200 App D

TM DESANA MAX CL


Version number: GHS 1.0

Date of compilation: 2019-03-15

ERG No	154
International Maritime Dangerous Goods Code (IMDG)	
UN number	3262
Proper shipping name	CORROSIVE SOLID, BASIC, INORGANIC, N.O.S.
Class	8
Marine pollutant	yes (hazardous to the aquatic environment)
Packing group	II
Danger label(s)	8, fish and tree



Special provisions (SP)	274
Excepted quantities (EQ)	E2
Limited quantities (LQ)	1 kg
EmS	F-A, S-B
Stowage category	B
Segregation group	18 - Alkalis
International Civil Aviation Organization (ICAO-IATA/DGR)	
UN number	3262
Proper shipping name	Corrosive solid, basic, inorganic, n.o.s.
Class	8
Environmental hazards	yes (hazardous to the aquatic environment)
Packing group	II
Danger label(s)	8



Special provisions (SP)	A3
Excepted quantities (EQ)	E2
Limited quantities (LQ)	5 kg

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations specific for the product in question

Industry or sector specific available guidance(s)

NPCA-HMIS® III

Hazardous Materials Identification System. American Coatings Association.

Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

TM DESANA MAX CL

Version number: GHS 1.0

Date of compilation: 2019-03-15

Category	Rating	Description
Chronic	*	Chronic (long-term) health effects may result from repeated overexposure
Health	3	Major injury likely unless prompt action is taken and medical treatment is given
Flammability	0	Material that will not burn under typical fire conditions
Physical hazard	0	Material that is normally stable, even under fire conditions, and will not react with water, polymerize, decompose, condense, or self-react. Non-explosive
Personal protection	-	

NFPA® 704

National Fire Protection Association: Standard System for the Identification of the Hazards of Materials for Emergency Response (United States).

Category	Degree of hazard	Description
Flammability	0	Material that will not burn under typical fire conditions
Health	3	Material that, under emergency conditions, can cause serious or permanent injury
Instability	0	Material that is normally stable, even under fire conditions
Special hazard	OX	Oxidizer that causes a severe increase in the burning rate of combustible materials with which it comes into contact

15.2 Chemical Safety Assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information, including date of preparation or last revision

Abbreviations and acronyms

Abbr.	Descriptions of used abbreviations
29 CFR 1910.1000	29 CFR 1910.1000, Tables Z-1, Z-2, Z-3 - Occupational Safety and Health Standards: Toxic and Hazardous Substances (permissible exposure limits)
49 CFR US DOT	49 CFR § 40 U.S. Department of Transportation
Acute Tox.	Acute toxicity
Aquatic Acute	Hazardous to the aquatic environment - acute hazard
Aquatic Chronic	Hazardous to the aquatic environment - chronic hazard
ATE	Acute Toxicity Estimate
CAS	Chemical Abstracts Service (service that maintains the most comprehensive list of chemical substances)
Ceiling-C	Ceiling value
DGR	Dangerous Goods Regulations (see IATA/DGR)
DMEL	Derived Minimal Effect Level
DNEL	Derived No-Effect Level
DOT	Department of Transportation (USA)
EC No	The EC Inventory (EINECS, ELINCS and the NLP-list) is the source for the seven-digit EC number, an identifier of substances commercially available within the EU (European Union)
EINECS	European Inventory of Existing Commercial Chemical Substances
ELINCS	European List of Notified Chemical Substances
EmS	Emergency Schedule
ERG No	Emergency Response Guidebook - Number
Eye Dam.	Seriously damaging to the eye

Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

TM DESANA MAX CL

Version number: GHS 1.0

Date of compilation: 2019-03-15

Abbr.	Descriptions of used abbreviations
Eye Irrit.	Irritant to the eye
GHS	"Globally Harmonized System of Classification and Labelling of Chemicals" developed by the United Nations
IATA	International Air Transport Association
IATA/DGR	Dangerous Goods Regulations (DGR) for the air transport (IATA)
ICAO	International Civil Aviation Organization
IMDG	International Maritime Dangerous Goods Code
MARPOL	International Convention for the Prevention of Pollution from Ships (abbr. of "Marine Pollutant")
Met. Corr.	Substance or mixture corrosive to metals
M-Factor	Means a multiplying factor. It is applied to the concentration of a substance classified as hazardous to the aquatic environment acute category 1 or chronic category 1, and is used to derive by the summation method the classification of a mixture in which the substance is present
NLP	No-Longer Polymer
NPCA-HMIS® III	National Paint and Coatings Association: Hazardous Materials Identification System - HMIS® III, Third Edition
OSHA	Occupational Safety and Health Administration (United States)
Ox. Sol.	Oxidizing solid
PBT	Persistent, Bioaccumulative and Toxic
PEL	Permissible exposure limit
PNEC	Predicted No-Effect Concentration
Ppm	Parts per million
RTECS	Registry of Toxic Effects of Chemical Substances (database of NIOSH with toxicological information)
Skin Corr.	Corrosive to skin
Skin Irrit.	Irritant to skin
STEL	Short-term exposure limit
STOT SE	Specific target organ toxicity - single exposure
TWA	Time-weighted average
VPvB	Very Persistent and very Bioaccumulative

Key literature references and sources for data

Transport of dangerous goods by road or rail (49 CFR US DOT). International Maritime Dangerous Goods Code (IMDG). Dangerous Goods Regulations (DGR) for the air transport (IATA).

Classification procedure

Physical and chemical properties: The classification is based on tested mixture.
health hazards, Environmental hazards: The method for classification of the mixture is based on ingredients of the mixture (additivity formula).

List of relevant phrases (code and full text as stated in chapter 2 and 3)

Code	Text
H272	May intensify fire; oxidizer.
H290	May be corrosive to metals.
H302	Harmful if swallowed.
H314	Causes severe skin burns and eye damage.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.

Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

TM DESANA MAX CL

Version number: GHS 1.0

Date of compilation: 2019-03-15

Code	Text
H330	Fatal if inhaled.
H335	May cause respiratory irritation.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.

Disclaimer

This information is based upon the present state of our knowledge. This SDS has been compiled and is solely intended for this product.