

Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

TM DESANACID FP

Version number: GHS 3.0
Replaces version of: 2018-01-15 (GHS 2)

Revision: 2018-11-06

SECTION 1: Identification

1.1 Product identifier

Trade name

TM DESANACID FP

1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses

cleaning agent
biocidal product
professional use (SU22)
industrial use (SU3)

Uses advised against

this information is not available

1.3 Details of the supplier of the safety data sheet

Thonhauser GmbH
Perlhofgasse 2/1
2372 Giesshübl/Wien
Austria

Telephone: +43 (0)2236 320 272
Telefax: +43 (0)2236 320 273
e-mail: QA@thonhauser.net
Website: www.thonhauser.net

e-mail (competent person)

QA@thonhauser.net (Herr Dr. Daniel Herzog)

1.4 Emergency telephone number

Manufacturer

+43 699 141 80 200

Mon - Thu 07:00 - 15:00, Fri 07:00 - 13:00

Poison center & Emergency information service

United States	Chemtrec Emergency Customer #CCN837	1-800-424-9300 (24h)
---------------	-------------------------------------	----------------------

SECTION 2: Hazard(s) identification

2.1 Classification of the substance or mixture

Classification acc. to GHS

Section	Hazard class	Cat-egory	Hazard class and category	Hazard state-ment
3.2	Skin corrosion/irritation	2	Skin Irrit. 2	H315
3.3	Serious eye damage/eye irritation	2	Eye Irrit. 2	H319
3.4R	Respiratory sensitization	1	Resp. Sens. 1	H334
3.4S	Skin sensitization	1	Skin Sens. 1	H317
3.8R	Specific target organ toxicity - single exposure (respiratory tract irritation)	3	STOT SE 3	H335
4.1C	Hazardous to the aquatic environment - chronic hazard	3	Aquatic Chronic 3	H412

For full text of H-phrases: see SECTION 16.

The most important adverse physicochemical, human health and environmental effects

Spillage and fire water can cause pollution of watercourses.

2.2 Label elements

Labeling

- Signal word **danger**

Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

TM DESANACID FP

Version number: GHS 3.0
Replaces version of: 2018-01-15 (GHS 2)

Revision: 2018-11-06

- Pictograms

GHS07, GHS08



- Hazard statements

H315 Causes skin irritation.
 H317 May cause an allergic skin reaction.
 H319 Causes serious eye irritation.
 H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.
 H335 May cause respiratory irritation.
 H412 Harmful to aquatic life with long lasting effects.

- Precautionary statements

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.
 P273 Avoid release to the environment.
 P280 Wear protective gloves/protective clothing/eye protection/face protection.
 P284 In case of inadequate ventilation wear respiratory protection.
 P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
 P312 Call a POISON CENTER/doctor if you feel unwell.
 P342+P311 If experiencing respiratory symptoms: Call a POISON CENTER/doctor.
 P362+P364 Take off contaminated clothing and wash it before reuse.
 P403+P233 Store in a well-ventilated place. Keep container tightly closed.
 P501 Dispose of contents/container to industrial combustion plant.

- Hazardous ingredients for labelling

disodium peroxodisulphate

2.3 Other hazards

Results of PBT and vPvB assessment

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

SECTION 3: Composition/information on ingredients

3.1 Substances

not relevant (mixture)

3.2 Mixtures

Description of the mixture

Name of sub-stance	Identifier	Conc.	Classification acc. to GHS	Pictograms	M-Factors
Sulphamidic acid	CAS No 5329-14-6 EC No 226-218-8	25 – < 50 wt%	Skin Irrit. 2 / H315 Eye Irrit. 2 / H319 Aquatic Chronic 3 / H412		
Disodium peroxodi-sulphate	CAS No 7775-27-1 EC No 231-892-1	25 – < 50 wt%	Ox. Sol. 3 / H272 Acute Tox. 4 / H302 Skin Irrit. 2 / H315 Eye Irrit. 2 / H319 Resp. Sens. 1 / H334 Skin Sens. 1 / H317 STOT SE 3 / H335		
Potassium perman-ganate	CAS No 7722-64-7 EC No 231-760-3	< 1 wt%	Ox. Sol. 2 / H272 Acute Tox. 4 / H302 Skin Corr. 1B / H314 Eye Dam. 1 / H318 Aquatic Acute 1 / H400 Aquatic Chronic 1 / H410		

For full text of abbreviations: see SECTION 16.

Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

TM DESANACID FP

Version number: GHS 3.0
Replaces version of: 2018-01-15 (GHS 2)

Revision: 2018-11-06

Regulation 528/2012/EU concerning the making available on the market and use of biocidal products

Biocidal active substances			
Name of substance	Wt%	w/w	unit
Disodium peroxodisulphate	41.2 %	412	g/kg

SECTION 4: First-aid measures

4.1 Description of first- aid measures



General notes

Do not leave affected person unattended. Remove victim out of the danger area. Keep affected person warm, still and covered. Take off immediately all contaminated clothing. In all cases of doubt, or when symptoms persist, seek medical advice. In case of unconsciousness place person in the recovery position. Never give anything by mouth.

Following inhalation

If breathing is irregular or stopped, immediately seek medical assistance and start first aid actions. In case of respiratory tract irritation, consult a physician. Provide fresh air.

Following skin contact

Rinse skin with water/shower.

Following eye contact

Remove contact lenses, if present and easy to do. Continue rinsing. Irrigate copiously with clean, fresh water for at least 10 minutes, holding the eyelids apart.

Following ingestion

Rinse mouth with water (only if the person is conscious). Do NOT induce vomiting.

4.2 Most important symptoms and effects, both acute and delayed

Symptoms and effects are not known to date.

4.3 Indication of any immediate medical attention and special treatment needed

none

SECTION 5: Fire-fighting measures

5.1 Extinguishing media

Suitable extinguishing media

water, foam, alcohol resistant foam, ABC-powder

Unsuitable extinguishing media

water jet

5.2 Special hazards arising from the substance or mixture

Hazardous combustion products

nitrogen oxides (NO_x), phosphorus oxides (P_xO_y), sulfur oxides (SO_x)

Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

TM DESANACID FP

Version number: GHS 3.0
Replaces version of: 2018-01-15 (GHS 2)

Revision: 2018-11-06

5.3 Advice for firefighters

In case of fire and/or explosion do not breathe fumes. Co-ordinate firefighting measures to the fire surroundings. Do not allow firefighting water to enter drains or water courses. Collect contaminated firefighting water separately. Fight fire with normal precautions from a reasonable distance.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

Remove persons to safety.

For emergency responders

Wear breathing apparatus if exposed to vapors/dust/aerosols/gases.

6.2 Environmental precautions

Keep away from drains, surface and ground water. Retain contaminated washing water and dispose of it.

6.3 Methods and material for containment and cleaning up

Advices on how to contain a spill

covering of drains, take up mechanically

Advices on how to clean up a spill

Take up mechanically. Absorbents and binders, neutralizing agents.

Other information relating to spills and releases

Place in appropriate containers for disposal. Ventilate affected area.

6.4 Reference to other sections

Hazardous combustion products: see section 5. Incompatible substances or mixtures: see section 7. Personal protective equipment: see section 8. Incompatible materials: see section 10. Disposal considerations: see section 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Recommendations

- Measures to prevent fire as well as aerosol and dust generation

Use local and general ventilation. Take precautionary measures against static discharge. Use only in well-ventilated areas. Ground/bond container and receiving equipment.

- Specific notes/details

Dust deposits may accumulate on all deposition surfaces in a technical room.

- Handling of incompatible substances or mixtures

- Keep away from

bases (alkalis)

- Advice on general occupational hygiene

Wash hands after use. Do not eat, drink and smoke in work areas. Remove contaminated clothing and protective equipment before entering eating areas. Never keep food or drink in the vicinity of chemicals. Never place chemicals in containers that are normally used for food or drink. Keep away from food, drink and animal feedingstuffs.

7.2 Conditions for safe storage, including any incompatibilities

Managing of associated risks

- Explosive atmospheres

Removal of dust deposits.

Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

TM DESANACID FP

Version number: GHS 3.0
Replaces version of: 2018-01-15 (GHS 2)

Revision: 2018-11-06

- Incompatible substances or mixtures

Prohibition of joint storage (with): bases (alkalis)

- Floors

The materials shall display sufficient resistance to the prevalent chemical conditions (Acids).

- Consideration of other advice

Observe technical data sheet.

- Ventilation requirements

Use local and general ventilation.

7.3 Specific end use(s)

These information are not available.

7.4 Other information

storage temperature of 0 °C and up to 20 °C
recommended storage temperature: 15-25 °C

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

National limit values

Occupational exposure limit values (Workplace Exposure Limits)											
Country	Name of agent	CAS No	Identifier	TWA [ppm]	TWA [mg/m ³]	STEL [ppm]	STEL [mg/m ³]	Ceiling-C [ppm]	Ceiling-C [mg/m ³]	Notation	Source
US	Particulates not otherwise classified (PNOC)		PEL	1,766	15					I, dust	29 CFR 1910.1000
US	Particulates not otherwise classified (PNOC)		PEL	529.5	5					Partm I, r, dust	29 CFR 1910.1000
US	Manganese compounds	7722-64-7	PEL						5	Mn	29 CFR 1910.1000

Notation

Ceiling-C Ceiling value is a limit value above which exposure should not occur.

dust As dust.

i Inhalable fraction.

Mn Calculated as Mn (manganese).

partml Particles/ml.

r Respirable fraction.

STEL Short-term exposure limit: a limit value above which exposure should not occur and which is related to a 15-minute period (unless otherwise specified).

TWA Time-weighted average (long-term exposure limit): measured or calculated in relation to a reference period of 8 hours time-weighted average (unless otherwise specified).

Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

TM DESANACID FP

Version number: GHS 3.0
Replaces version of: 2018-01-15 (GHS 2)

Revision: 2018-11-06

Relevant DNELs/DMELs/PNECs and other threshold levels

Relevant DNELs of components of the mixture

Name of substance	CAS No	End-point	Threshold level	Protection goal, route of exposure	Used in	Exposure time
Sulphamidic acid	5329-14-6	DNEL	7.5 mg/m ³	Human, inhalatory	Worker (industry)	Chronic - systemic effects
Disodium peroxodi-sulphate	7775-27-1	DNEL	2.06 mg/m ³	Human, inhalatory	Worker (industry)	Chronic - local effects
Disodium peroxodi-sulphate	7775-27-1	DNEL	18.2 mg/kg	Human, dermal	Worker (industry)	Chronic - systemic effects
Disodium peroxodi-sulphate	7775-27-1	DNEL	2.06 mg/m ³	Human, inhalatory	Worker (industry)	Chronic - systemic effects
Potassium permanganate	7722-64-7	DNEL	0.218 mg/m ³	Human, inhalatory	Worker (industry)	Chronic - systemic effects

Relevant PNECs of components of the mixture

Name of substance	CAS No	End-point	Threshold level	Organism	Environmental compartment	Exposure time
Sulphamidic acid	5329-14-6	PNEC	0.3 mg/l	Aquatic organisms	Freshwater	Short-term (single instance)
Sulphamidic acid	5329-14-6	PNEC	0.03 mg/l	Aquatic organisms	Marine water	Short-term (single instance)
Sulphamidic acid	5329-14-6	PNEC	200 mg/l	Microorganisms	Sewage treatment plant (STP)	Short-term (single instance)
Sulphamidic acid	5329-14-6	PNEC	0.3 mg/kg	Benthic organisms	Sediment	Short-term (single instance)
Sulphamidic acid	5329-14-6	PNEC	0.03 mg/kg	Pelagic organisms	Sediment	Short-term (single instance)
Sulphamidic acid	5329-14-6	PNEC	3 mg/kg	Terrestrial organisms	Soil	Short-term (single instance)
Sulphamidic acid	5329-14-6	PNEC	0.3 mg/l	Aquatic organisms	Water	Intermittent release
Disodium peroxodi-sulphate	7775-27-1	PNEC	0.0763 mg/l	Aquatic organisms	Freshwater	Short-term (single instance)
Disodium peroxodi-sulphate	7775-27-1	PNEC	3.6 mg/l	Microorganisms	Sewage treatment plant (STP)	Short-term (single instance)
Disodium peroxodi-sulphate	7775-27-1	PNEC	0.275 mg/kg	Benthic organisms	Sediment	Short-term (single instance)
Disodium peroxodi-sulphate	7775-27-1	PNEC	0.0396 mg/kg	Pelagic organisms	Sediment	Short-term (single instance)
Disodium peroxodi-sulphate	7775-27-1	PNEC	0.015 mg/kg	Terrestrial organisms	Soil	Short-term (single instance)
Disodium peroxodi-sulphate	7775-27-1	PNEC	0.763 mg/l	Aquatic organisms	Water	Intermittent release
Disodium peroxodi-sulphate	7775-27-1	PNEC	0.011 mg/l	Aquatic organisms	Marine water	Short-term (single instance)
Potassium permanganate	7722-64-7	PNEC	0.06 µg/l	Aquatic organisms	Freshwater	Short-term (single instance)
Potassium permanganate	7722-64-7	PNEC	1.64 mg/l	Microorganisms	Sewage treatment plant (STP)	Short-term (single instance)

Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

TM DESANACID FP

Version number: GHS 3.0
Replaces version of: 2018-01-15 (GHS 2)

Revision: 2018-11-06

Relevant PNECs of components of the mixture						
Name of substance	CAS No	End-point	Threshold level	Organism	Environmental compartment	Exposure time
Potassium permanganate	7722-64-7	PNEC	0.6 µg/l	Aquatic organisms	Water	Intermittent release

8.2 Exposure controls

Appropriate engineering controls

General ventilation.

Individual protection measures (personal protective equipment)



Eye/face protection

Wear eye/face protection. Use safety goggle with side protection. Use protective eyewear to guard against splash of liquids. EN 166.

Skin protection

- Hand protection

When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits. Wear suitable gloves. Chemical protection gloves are suitable, which are tested according to EN 374. Check leak-tightness/impermeability prior to use. In the case of wanting to use the gloves again, clean them before taking off and air them well. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

- Protective gloves - Splash protection

Recommended protective gloves (trademark/manufacturer):

- Other protection measures

Take recovery periods for skin regeneration. Preventive skin protection (barrier creams/ointments) is recommended. Wash hands thoroughly after handling.

Respiratory protection

Wear breathing apparatus if exposed to vapors/dust/aerosols/gases. In case of inadequate ventilation wear respiratory protection. Particulate filter device (EN 143).

Chemical protective clothing

Wear suitable protective clothing.

Environmental exposure controls

Avoid release to the environment. Refer to special instructions/safety data sheets. Before discharge of the waste water into a municipal waste water treatment facility the product normally needs to be neutralized.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance

Physical state	solid
Color	pink
Odor	characteristic

Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

TM DESANACID FP

Version number: GHS 3.0
Replaces version of: 2018-01-15 (GHS 2)

Revision: 2018-11-06

Other safety parameters

pH (value)	1.2 – 2.2 (water: 10 g/l, 20 °C) * (acid)
Melting point/freezing point	not determined
Initial boiling point and boiling range	not determined
Flash point	not applicable
Evaporation rate	not determined
Flammability (solid, gas)	non-combustible
Explosion limits of dust clouds	not determined
Vapor pressure	not determined
Density	not determined
Vapor density	this information is not available
Relative density	information on this property is not available
Solubility(ies)	not determined
Partition coefficient	
- n-octanol/water (log KOW)	this information is not available
Auto-ignition temperature	not determined
Viscosity	not relevant (solid matter)
Explosive properties	none
Oxidizing properties	none

9.2 Other information

Solvent content	0 %
Solid content	100 %

SECTION 10: Stability and reactivity

10.1 Reactivity

Concerning incompatibility: see below "Conditions to avoid" and "Incompatible materials".

10.2 Chemical stability

See below "Conditions to avoid".

10.3 Possibility of hazardous reactions

Exhibits an exothermic reaction (with): Caustic solutions (Alkalis)

Dangerous/dangerous reactions with: base metals (formation of hydrogen), oxidizers

10.4 Conditions to avoid

There are no specific conditions known which have to be avoided.

10.5 Incompatible materials

There is no additional information.

10.6 Hazardous decomposition products

Reasonably anticipated hazardous decomposition products produced as a result of use, storage, spill and heating are not known. Hazardous combustion products: see section 5.

Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

TM DESANACID FP

Version number: GHS 3.0
Replaces version of: 2018-01-15 (GHS 2)

Revision: 2018-11-06

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Test data are not available for the complete mixture.

Classification procedure

The method for classification of the mixture is based on ingredients of the mixture (additivity formula).

Classification acc. to OSHA "Hazard Communication Standard" (29 CFR 1910.1200)

Acute toxicity

Shall not be classified as acutely toxic.

GHS of the United Nations, annex 4:

Acute toxicity estimate (ATE) of components of the mixture			
Name of substance	CAS No	Exposure route	ATE
Disodium peroxodisulphate	7775-27-1	Oral	1,200 mg/kg
Potassium permanganate	7722-64-7	Oral	2,000 mg/kg

Skin corrosion/irritation

Causes skin irritation.

Serious eye damage/eye irritation

Causes serious eye irritation.

Respiratory or skin sensitization

May cause allergy or asthma symptoms or breathing difficulties if inhaled. May cause an allergic skin reaction.

Germ cell mutagenicity

Shall not be classified as germ cell mutagenic.

Carcinogenicity

Shall not be classified as carcinogenic.

Reproductive toxicity

Shall not be classified as a reproductive toxicant.

Specific target organ toxicity - single exposure

May cause respiratory irritation.

Specific target organ toxicity - repeated exposure

Shall not be classified as a specific target organ toxicant (repeated exposure).

Aspiration hazard

Shall not be classified as presenting an aspiration hazard.

SECTION 12: Ecological information

12.1 Toxicity

Harmful to aquatic life with long lasting effects.

Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

TM DESANACID FP

Version number: GHS 3.0
Replaces version of: 2018-01-15 (GHS 2)

Revision: 2018-11-06

Aquatic toxicity (acute)

Aquatic toxicity (acute) of components of the mixture					
Name of substance	CAS No	Endpoint	Value	Species	Exposure time
Potassium permanganate	7722-64-7	LC50	0.7 mg/l	Fish	48 h
Potassium permanganate	7722-64-7	EC50	0.06 mg/l	Aquatic invertebrates	48 h

Aquatic toxicity (chronic) of components of the mixture					
Name of substance	CAS No	Endpoint	Value	Species	Exposure time
Potassium permanganate	7722-64-7	LC50	1.51 mg/l	Fish	24 h
Potassium permanganate	7722-64-7	EC50	0.15 mg/l	Aquatic invertebrates	24 h

12.2 Persistence and degradability

Data are not available.

12.3 Bioaccumulative potential

Data are not available.

12.4 Mobility in soil

Data are not available.

12.5 Results of PBT and vPvB assessment

Data are not available.

12.6 Other adverse effects

Data are not available.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Waste treatment-relevant information

Recycling/reclamation of other inorganic materials.

Sewage disposal-relevant information

The application solution can be disposed in the sewage system, taking into account technical and national regulations.

Waste treatment of containers/packages

Completely emptied packages can be recycled. Handle contaminated packages in the same way as the substance itself.

Remarks

Please consider the relevant national or regional provisions. Waste shall be separated into the categories that can be handled separately by the local or national waste management facilities.

Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

TM DESANACID FP

Version number: GHS 3.0
Replaces version of: 2018-01-15 (GHS 2)

Revision: 2018-11-06

SECTION 14: Transport information

- 14.1 UN number** not subject to transport regulations
- 14.2 UN proper shipping name** not relevant
- 14.3 Transport hazard class(es)** none
- 14.4 Packing group** not relevant
- 14.5 Environmental hazards** non-environmentally hazardous acc. to the dangerous goods regulations
- 14.6 Special precautions for user**
There is no additional information.
- 14.7 Transport in bulk according to Annex II of MARPOL and the IBC Code**
The cargo is not intended to be carried in bulk.

Information for each of the UN Model Regulations

Transport of dangerous goods by road or rail (49 CFR US DOT)

Not subject to transport regulations.

International Maritime Dangerous Goods Code (IMDG)

Not subject to IMDG.

International Civil Aviation Organization (ICAO-IATA/DGR)

Not subject to ICAO-IATA.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations specific for the product in question

Industry or sector specific available guidance(s)

NPCA-HMIS® III

Hazardous Materials Identification System. American Coatings Association.

Category	Rating	Description
Chronic	*	Chronic (long-term) health effects may result from repeated overexposure
Health	2	Temporary or minor injury may occur
Flammability	1	Material that must be preheated before ignition can occur
Physical hazard	0	Material that is normally stable, even under fire conditions, and will not react with water, polymerize, decompose, condense, or self-react. Non-explosive
Personal protection	-	

NFPA® 704

National Fire Protection Association: Standard System for the Identification of the Hazards of Materials for Emergency Response (United States).

Category	Degree of hazard	Description
Flammability	1	Material that must be preheated before ignition can occur
Health	2	Material that, under emergency conditions, can cause temporary incapacitation or residual injury
Instability	0	Material that is normally stable, even under fire conditions
Special hazard	OX	Oxidizer that causes a moderate increase in the burning rate of combustible materials with which it comes into contact

Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

TM DESANACID FP

Version number: GHS 3.0
Replaces version of: 2018-01-15 (GHS 2)

Revision: 2018-11-06

15.2 Chemical Safety Assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information, including date of preparation or last revision

Abbreviations and acronyms

Abbr.	Descriptions of used abbreviations
29 CFR 1910.1000	29 CFR 1910.1000, Tables Z-1, Z-2, Z-3 - Occupational Safety and Health Standards: Toxic and Hazardous Substances (permissible exposure limits)
49 CFR US DOT	49 CFR § 40 U.S. Department of Transportation
Acute Tox.	Acute toxicity
Aquatic Acute	Hazardous to the aquatic environment - acute hazard
Aquatic Chronic	Hazardous to the aquatic environment - chronic hazard
ATE	Acute Toxicity Estimate
CAS	Chemical Abstracts Service (service that maintains the most comprehensive list of chemical substances)
Ceiling-C	Ceiling value
DGR	Dangerous Goods Regulations (see IATA/DGR)
DMEL	Derived Minimal Effect Level
DNEL	Derived No-Effect Level
EC No	The EC Inventory (EINECS, ELINCS and the NLP-list) is the source for the seven-digit EC number, an identifier of substances commercially available within the EU (European Union)
EINECS	European Inventory of Existing Commercial Chemical Substances
ELINCS	European List of Notified Chemical Substances
Eye Dam.	Seriously damaging to the eye
Eye Irrit.	Irritant to the eye
GHS	"Globally Harmonized System of Classification and Labelling of Chemicals" developed by the United Nations
IATA	International Air Transport Association
IATA/DGR	Dangerous Goods Regulations (DGR) for the air transport (IATA)
ICAO	International Civil Aviation Organization
IMDG	International Maritime Dangerous Goods Code
MARPOL	International Convention for the Prevention of Pollution from Ships (abbr. of "Marine Pollutant")
NLP	No-Longer Polymer
NPCA-HMIS® III	National Paint and Coatings Association: Hazardous Materials Identification System - HMIS® III, Third Edition
OSHA	Occupational Safety and Health Administration (United States)
Ox. Sol.	Oxidizing solid
PBT	Persistent, Bioaccumulative and Toxic
PEL	Permissible exposure limit
PNEC	Predicted No-Effect Concentration
Ppm	Parts per million
Resp. Sens.	Respiratory sensitization
RTECS	Registry of Toxic Effects of Chemical Substances (database of NIOSH with toxicological information)
Skin Corr.	Corrosive to skin

Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

TM DESANACID FP

Version number: GHS 3.0
Replaces version of: 2018-01-15 (GHS 2)

Revision: 2018-11-06

Abbr.	Descriptions of used abbreviations
Skin Irrit.	Irritant to skin
Skin Sens.	Skin sensitization
STEL	Short-term exposure limit
STOT SE	Specific target organ toxicity - single exposure
TWA	Time-weighted average
VPvB	Very Persistent and very Bioaccumulative

Key literature references and sources for data

Transport of dangerous goods by road or rail (49 CFR US DOT). International Maritime Dangerous Goods Code (IMDG). Dangerous Goods Regulations (DGR) for the air transport (IATA).

Classification procedure

Physical and chemical properties: The classification is based on tested mixture.
health hazards, Environmental hazards: The method for classification of the mixture is based on ingredients of the mixture (additivity formula).

List of relevant phrases (code and full text as stated in chapter 2 and 3)

Code	Text
H272	May intensify fire; oxidizer.
H302	Harmful if swallowed.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H335	May cause respiratory irritation.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.

Disclaimer

This information is based upon the present state of our knowledge. This SDS has been compiled and is solely intended for this product.